

MDS-6LPF



Low-Mid Rise Lifts

SKU# 5175227

6,000-lb. Capacity / Mid-Rise Lift / Open-Center / Flush-Mount

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

The MDS-6LPF Walks the Walk

If you're looking to flush-mount your auto lift in the floor for a smooth sub-surface installation, be sure to choose the MDS-6LPF. It shares all the same features of the MDS-6LP but is more ideal if you want your lift to collapse perfectly parallel with your flooring. With nearly 40" of rise from the flush-mounted position, the MDS-6LPF is a world-class performer in the mid-rise lift class. There's no better way to get this much power and height from a fully collapsed design.



Features

- Four solid steel-scissor frame support bars, making it one of the strongest mid-rise lifts in its class
- Flush-mount design for in-ground installation in lube shops, full-service bays and home garage environments looking for a zero-footprint lift.
- Solid-steel safety lock bars engage automatically
- Convenient stainless-steel pneumatic cylinders simultaneously release safety locks during descent with a simple push of a button.
- Push-button safety lock release system
- Hinge point features Zerk grease fitting to allow lubrication at critical wear areas
- Comes standard with four durable cushioned-rubber contact blocks, permitting fast vehicle setup
- Three locking positions allow technicians to work at different working heights to increase productivity

Specifications

Lifting Capacity	6,000 lbs. (2,724 kg)
Lift Height w/o Blocks	43" (1,093 mm) / (minus 4-3/8" for sub-surface flooring)
Lift Height + Blocks	45" (1,144 mm) / (minus 4-3/8" for sub-surface flooring)
Lift Platform Dimensions	19" x 67" (484 mm x 1,701 mm)
Width Between Platforms	40" to 46" (1,018 mm to 1,168 mm)
Overall Width	Adjustable
Overall Length	67" (1,701 mm)
Lowered Height	Flush with ground
Lifting Time	35 sec
Motor	208-230 VAC / 60 Hz / 1 Ph

Design, materials, and specifications shown here are subject to change without notice.

Note: An air supply (minimum 50 psi / 10 CFM) is required for the safety-lock mechanisms to disengage. It is solely your responsibility to install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.